



		25	HTP
1			M8
			ø12

15,



SUGLIANI R.


CIMMINO L.



	PRODUCT TYPE	M8 CIRCULAR CONNECTOR FIELD ATTACHABLE
	HOUSING MATERIAL/COLOUR	REV.02 PA66+30%GF /BLACK
	PRESS-CABLE MATERIAL/COLOUR	REV.02 PA66+30%GF /BLACK
	INTRENAL CORE MATERIAL/COLOUR	REV.02 PA66+30%GF /BLACK
	CONTACTS TYPE	FEMALE SCREW CONTACTS
	NUMBER OF POLES	3POLES
ES	SUITABLE CABLE	FROM ø3,5mm TO ø5,5mm
TUR	MAX.CONDUCTOR SIZE	0,5mm²
FEA	PROTECTION CLASS	IP67
CONNECTOR	RATED VOLTAGE	50V AC / 60V DC
NNE	RATED CURRENT	3A
	CONNECTOR TEMPERATURE RANGE	from -40°C to +90°C
	SEAL MATERIAL	NBR
	CONNECTOR WITH H.T.P. LOGO	



PACKAGING: **REV.01**SINGLY PACKED IN THE PLASTIC BAG
(PLASTIC BAG WITHOUT ANY LOGO AND LABEL)



ON THE INTERNAL CORE
MUST BE SILK PRINTED
THE CONTACTS NUMBERS

Series

Customer code:

CUSTOMER APPROVAL
SIGNATURE DATE

PLEASE SIGN AND RETURN

A 4

Rev.



TM PRODUCTS S.R.L.

Designer

Approved

DESCRIPTION

Date 2018-03-23

Date 2018-03-23

CIRCULAR CONNECTOR M8 FIELD ATTACHABLE, FEMALE, STRAIGHT 180°, 3POLES, EXIT CABLE FROM ø3,5mm TO ø5,5mm CONNECTOR WITH H.T.P.LOGO

2:1

Tollerance ±0.3

Scale

H.T.P.PART NUMBER

08FC3000-S-SK

Α4

Units:

Size:

Drawing n.

1–1