


| CONNECTOR FEATURES | | | | | | | | | | | |
|---------------------------|------------------|--------|---------------------------|---------------|---------------|----------------|-----------------------|--------------------|--------------|--------------|---------------------|
| CONNECTOR WITH H.T.P.LOGO | PROTECTION CLASS | 0"RING | COUPLING NUT MATERIAL | RATED CURRENT | RATED VOLTAGE | HOUSING COLOUR | HOUSING MATERIAL | NUMBER OF CONTACTS | HOUSING TYPE | CONTACT TYPE | PRODUCT TYPE |
| | IP67 | NBR | STAINLESS STEEL (AISI304) | 4 A | 30V AC/DC | BLACK | NYLON6+30%GLASS FIBRE | 4P0LES | 180° | SCREW MALE | M8 FIELD ATTACHABLE |







| High Tech Products | M8 MALE STRA | U.d.M | |
|---------------------------|---|---|--|
| | VIGHT 180°, SING, TO CA ONNECTOR | ±0.2 | |
| H.T.P. HIGH TECH PRODUCTS | RESERVOW. M8 MALE STRAIGHT 180°, 4 POLES, WITHOUT H.T.P.LOGO, BLACK HOUSING, TO CABLE WITH SCREW CONTACT. CONNECTOR WITH H.T.P.LOGO | LORENZO CIMMINO CONTROLLATO | |
| 2 | - | 09.07.12 | |
| 08M | М8 | | |
| C40(| | ======================================= | |
| 08MC4000-S-INOX | | 4 | |
| NOX | MATERIALE | | |
| | | | |

| _ | I | G | П | Ш | D | C | æ | ≻ |
|--------------------------|--------------------------------|------------------|--------|---------------------------|---------------|-------------------------|---------------------------|------------------|
| BRASS NICKEL PLATED DUCT | M8 NUT STAINLESS STEEL AISI304 | INTERNAL CORE M8 | 0-RING | SCREW CONTACT GOLD PLATED | HOUSING BLACK | GASKET PRESS-CABLE SEAL | LAMELLAE PRESS-CABLE SEAL | PRESS CABLE SREW |