


CONNECTOR FEATURES	PRODUCT TYPE	M12 CIRCULAR CONNECTOR FIELD ATTACHABLE
	CONNECTOR TYPE	STRAIGHT 180°
	HOUSING MATERIAL/COLOUR	PA66+30%GF/BLACK
	PRESS-CABLE MATERIAL/COLOUR	PA66/BLACK
	INTERNAL CORE MATERIAL/COLOUR	PA66/BLACK
	M12 COUPLING NUT MATERIAL	BRASS + NICKEL PLATED
	CONTACTS TYPE	FEMALE SCREW CONTACTS
	NUMBER OF POLES	4POLES(5HOLES <u>REV.01</u> )
	CABLE EXIT	PG7
	SUITABLE CABLE	FROM ø4mm TO ø6mm
	MAX.CONDUCTOR SIZE	0,75mm²(AWG18)
	PROTECTION CLASS	IP67
	RATED VOLTAGE	250V AC/DC
	RATED CURRENT	4 A
	CONNECTOR TEMPERATURE RANGE	from -40°C to +90°C
	CONNECTOR WITH H.T.P. LOGO	


PACKAGING: SINGLY PACKED IN THE PLASTIC BAG (PLASTIC BAG WITHOUT ANY LOGO AND LABEL)





CIMMINO L.

SUGLIANI R.



Α4

Series

M12

Customer code:



A 4

Rev.

Rev.

SUGLIANI CIMMINO

CIMMINO SUGLIANI

2019.05.2

2021.04.

02 10

Signed



Designer

Approved

**DESCRIPTION** 

Date 2018-09-17

Date 2018-09-17

CIRCULAR CONNECTOR M12 FIELD ATTACHABLE, FEMALE, STRAIGHT 180° 4POLES(5HOLES), PG7 EXIT CABLE. CONNECTOR WITH H.T.P.LOGO

Tollerance ±0.3

1:1

Scale

H.T.P.PART NUMBER

12FC4000

H.T.P. High Tech Products S.R.L. Via Lesina,45 -24030- Brembate di Sopra (Bg) - ITALY Phone:+39.035692509 Fax:+39.035203291

E-mail: info@webhtp.eu Web: http://www.webhtp.eu/

Units:

Size:

ALL RIGHTS ARE RESERVED.

Drawing n.

1-1