


Rev.	Modify	Date	Signed	Approved



- 1) BROWN ■ 1
- 3) BLUE ■ 3
- 4) BLACK ■ 4

CONNECTOR FEATURES	PRODUCT TYPE	EXTENSION M12-M12 CIRCULAR CONNECTORS WITH MOULDED CABLE
	M12 CONNECTOR TYPE	STRAIGHT 180° FEMALE 3POLES
	M12 CONNECTOR TYPE	STRAIGHT 180° MALE 3POLES
	NUMBER OF CONTACTS CONNECTED	N°3
	PROTECTION CLASS	IP69K
	RATED VOLTAGE	250V AC/DC
	RATED CURRENT	4 A
	CONNECTORS WITH H.T.P.LOGO	
CABLE FEATURES	H.T.P.CABLE CODE	CAVO C-3-K6-IS USE THE CABLE 31-3-K6-IS
	NUMBER OF CONDUCTORS	N°3
	CONDUCTORS SECTION	24AWG (0,25mm ²)
	CABLE MATERIAL	PUR ULstyle21576 Us
	COATING COLOUR	BLACK
	CONDUCTORS INSULATION MATERIAL	TPO
	CABLE LENGHT	600mm
	HIGH FLEX (CLASS 6)	
	CABLE PROVIDED BY H.T.P.srl	
	ON THE CABLE, NEAR THE CONNECTOR HEAD, MUST BE SILK PRINTED THE H.T.P. PRODUCTION DATE CODE 5#####	
	ON THE CABLE MUST BE APPLIED N°2 HOLDERS FOR CABLE MARKING.	


CUSTOMER APPROVAL

SIGNATURE	DATE

PLEASE SIGN AND RETURN

A4

Designer	CIMMINO L.	Date	2016-07-07	Tolerance	±0.3	Units:	mm	Series	M12	Drawing n. 1-1
Approved	MAZZOLA M.	Date	2016-07-07	Scale	1:1	Size:	A4	Customer code:		



DESCRIPTION
EXTENSION CIRCULAR CONNECTORS M12,FEMALE,STRAIGHT 180°,3POLES+M12 MALE,STRAIGHT 180°,3POLES,WITH CABLE PUR/TPO ULstyle21576,3x0,25mm², HIGH FLEX,BLACK COLOUR,L=0,6m.CONNECTORS WITH H.T.P.LOGO

H.T.P.PART NUMBER

12FD3C0F12MD-K6-IS