


Rev.	Modify	Date	Signed	Approved



 PAY ATTENTION:
ON EACH CONDUCTOR MUST BE APPLIED THE THERMO REDUCING TUBE

CONNECTOR FEATURES	PRODUCT TYPE	M12 CIRCULAR CONNECTOR TO PANEL WITH FLANGE 20x20mm WITH WIRES
	TYPE MOUNTING	FRONTAL MOUNTING
	CONTACTS TYPE	FEMALE 4POLES
	NUMBER OF CONTACTS CONNECTED	N°4
	HOUSING MATERIAL	BRASS+NICKEL PLATED
	FLANGE SIZE	20x20mm
	FIXING HOLES DIAMETER (X4)	ø3,2mm
	FIXING HOLES DISTANCE	14x14mm
	PROTECTION CLASS	IP67
	RATED VOLTAGE	250V AC/DC
	RATED CURRENT	4 A
	CONNECTOR WITHOUT ANY LOGO	
WIRES FEATURES	NUMBER OF CONDUCTORS	N°4
	CONDUCTORS SECTION	0,25mm ²
	CONDUCTORS INSULATION MATERIAL	PVC
	CONDUCTORS LENGHT	230mm

CUSTOMER APPROVAL	
SIGNATURE	DATE
PLEASE SIGN AND RETURN	

Designer	SUGLIANI R.	Date	2016-11-09	Tollerance	± 0.3	Units:	mm	Series	M12	Drawing n. 1-1
Approved	CIMMINO L.	Date	2016-11-09	Scale	1:1	Size:	A4	Customer code:		



DESCRIPTION	CIRCULAR CONNECTOR M12,FEMALE,TO PANEL,4POLES,FRONTAL MOUNTING, WITH FIXING FLANGE 20mmx20mm, FIXING HOLES DISTANCE 14mmx14mm, WITH N°4 WIRES PVC 0,25mm ² L=230mm CONNECTOR WITHOUT ANY LOGO
-------------	---

12FP4A0B3-FL