



CONNECTOR FEATURES

TYPE CONTACT	FEMALE
NUMBER OF CONTACT	4 POLES
HOUSING	NYLON6 + 30%GLASS FIBRE
TYPE HOUSING	180°
COLOUR HOUSING	TRANSPARENT
PRESS CABLE SCREW	PG7
RATED VOLTAGE:	250V AC/DC
RATED CURRENT:	4A
CONTACT MATERIAL	PHOSPHOROUS BRONZE
CONTACT SURFACE MATERIAL:	NICKEL +0.45µm
COUPLING NUT MATERIAL:	Zn Al/Ni
O-RING:	NBR
PROTECTION CLASS:	IP67
TEMPERATURE RANGE:	-25°C TO +90°C

A	PRESS CABLE SREW
B	LAMELLAE PRESS-CABLE SEAL
C	GASKET PRESS-CABLE SEAL
D	HOUSING TRANSPARENT
E	SCREW CONTACT GOLD PLATED
F	O-RING
G	INTERNAL CORE M12
H	O-RING
I	PLASTIC NUT FOR HOUSING
J	M12 NUT Zn Al/Ni

TOLLERANCE	DISSEGNAZIONE	DATA	SCALA	PESU
U24M	MARCO MAZZINI	14.01.09	1:1	
ANGULO	CONTROLLATO			

DESCRIZIONE: M12 FEMALE TO CABLE 4 POLES
180° TRANSPARENT PG7 WITH LOGO HTP

HTP High Tech Products H.T.P. HIGH TECH PRODUCTS CODICE 12FZ4000