


CABLE FEATURES		CONNECTOR FEATURES	
CONNECTOR TYPE	M12 180°	CONNECTOR TYPE	MALE 8POLES
CABLE LENGTH	5000mm	CABLE LENGTH	5000mm
PROTECTION CLASS	IP69K	PROTECTION CLASS	IP69K
STRIPPING	35mm STANDARD	STRIPPING	35mm STANDARD
PEELING AND TINNING	5mm STANDARD	PEELING AND TINNING	5mm STANDARD
NUMBER OF CONTACTS CONNECTED	N°8	NUMBER OF CONTACTS CONNECTED	N°8
RATED VOLTAGE	60V AC/DC	RATED VOLTAGE	60V AC/DC
RATED CURRENT	2A	RATED CURRENT	2A
CONNECTOR WITH H.T.P. LOGO		CONNECTOR WITH H.T.P. LOGO	
H.T.P. CABLE CODE	CAVVO Q-8	H.T.P. CABLE CODE	CAVVO Q-8
NUMBER OF CONDUCTORS	N°8	NUMBER OF CONDUCTORS	N°8
CONDUCTOR SECTION	0.25mm ²	CONDUCTOR SECTION	0.25mm ²
CABLE MATERIAL	PVC CEI2022	CABLE MATERIAL	PVC CEI2022
COATING COLOUR	GREY RAL 7032	COATING COLOUR	GREY RAL 7032
CONDUCTOR INSULATION MATERIAL	PVC	CONDUCTOR INSULATION MATERIAL	PVC
CABLE SHIELDED		CABLE SHIELDED	

TOLLERANZE	±0,3	DISIGNATORE	DATA	SCALA	DESIGN N.
UDM	ANGOLIO	LORENZO CHINNO CONTROLLATO	04.04.14	1:1	
DESCRIZIONE		M12 MALE 180° 8 POLES WITH CABLE PVC/PVC CEI2022 8X0.25mm ² SHIELDED GREY L=5m CONNECTOR WITH H.T.P. LOGO		TR90	MATERIALE
		H.T.P. HIGH TECH PRODUCTS		CODE	12MD805Z



H.T.P.
HIGH TECH PRODUCTS

12MD805Z