


CONNECTOR FEATURES

TYPE CONTACT	FEMALE B-CODED
NUMBER OF CONTACT	5 POLES
HOUSING	NYLON66+15%GLASS FIBRE
TYPE HOUSING	180°
COLOUR HOUSING	BLACK
PRESS CABLE SCREW	PG7
RATED VOLTAGE:	60V AC/DC
RATED CURRENT:	4A
CONTACT MATERIAL	PHOSPHOROUS BRONZE
CONTACT SURFACE MATERIAL:	NICKEL +0,45µm
COUPLING NUT MATERIAL:	Zn Al/Ni
O-RING:	NBR
PROTECTION CLASS:	IP67
TEMPERATURE RANGE:	-25°C TO +90°C

A	PRESS CABLE SCREW
B	LAMELLAE PRESS-CABLE SEAL
C	GASKET PRESS-CABLE SEAL
D	HOUSING BLACK
E	SCREW CONTACT GOLD PLATED
F	O-RING
G	INTERNAL CORE M12 B-CODED
H	O-RING
I	PLASTIC NUT FOR HOUSING
J	M12 NUT Zn Al/Ni

TOLLERANZE	±0,2	DISIGNATORE	DATA	SCALA	PROF
UDM	ANGOLO	LORENZO CHINIO	04.06.12	1:1	
		CONTROLLATO			

DESCRIZIONE  
 M12 FEMALE B-CODED FIELD ATTACHABLE  
 5 POLES 180° BLACK PG7


**H.T.P.**  
 HIGH TECH PRODUCTS  
 CODE  
**B-12FC5000**