



| CABLE FEATURES | | CONNECTOR FEATURES | |
|-------------------------------|--------------------|--------------------------------------|---------------|
| CONTACT TYPE | 2POLES+EARTH | CONTACT SPACING | 11mm |
| CABLE LENGTH | 3000mm | PROTECTION CLASS | IP67 |
| CONDUCTOR SECTION | 0.5mm ² | STRIPPING | 35mm STANDARD |
| CABLE MATERIAL | PVC H03VVF | PEELING AND TINNING | 5mm STANDARD |
| CABLE COLOUR | BLACK | FIXING SCREW | M3X28.7 |
| CONDUCTOR INSULATION MATERIAL | PVC | PROFILED GASKET | NBR |
| | | EARTH H | 6/12 |
| | | VOLTAGE | 24V |
| | | CONNECTOR WITH YELLOW LED + VARISTOR | |
| H.T.P. CABLE CODE | 01 | | |
| NUMBER OF CONDUCTORS | N°3 | | |

| | | | | |
|--|-----------------------|----------|-------|---------------|
| TOLLERANZE | DISEGNATORE | DATA | SCALE | DISEGNO N. |
| U4H | LIBERAZIONE CONTROLLO | 12-11-10 | 1 : 1 | |
| DESCRIZIONE | | TR0 | | MATERIALE |
| DIN43650/B 2POLES+EARTH(H 6/12) WITH YELLOW LED+VDR, 24V WITH CABLE PVC/PVC H03VVF 3X0.5mm ² BLACK L=3m | | | CM1 | |
| | | | | |
| | | | | |
| | | | | |
| H.T.P. HIGH TECH PRODUCTS | | CODE | | CM1N02VG1C013 |