



CABLE FEATURES		CONNECTOR FEATURES	
CONNECTOR TYPE	DIN43650/C	CONNECTOR TYPE	DIN43650/C
CONTACT TYPE	2POLES+EARTH	CONTACT TYPE	2POLES+EARTH
CONTACT SPACING	8mm	CONTACT SPACING	8mm
CABLE LENGTH	2000mm	CABLE LENGTH	2000mm
PROTECTION CLASS	IP67	PROTECTION CLASS	IP67
STRIPPING	35mm STANDARD	STRIPPING	35mm STANDARD
PEELING AND TINNING	5mm STANDARD	PEELING AND TINNING	5mm STANDARD
FIXING SCREW	M2.5X21.5	FIXING SCREW	M2.5X21.5
PROFILED GASKET	NBR	PROFILED GASKET	NBR
EARTH H	6/12	EARTH H	6/12
VOLTAGE	24V	VOLTAGE	24V
CONNECTOR WITH RED LED + DIODE		CONNECTOR WITH RED LED + DIODE	
H.T.P. CABLE CODE	01	H.T.P. CABLE CODE	01
NUMBER OF CONDUCTORS	n°3	NUMBER OF CONDUCTORS	n°3
CONDUCTOR SECTION	0.5mm <sup>2</sup>	CONDUCTOR SECTION	0.5mm <sup>2</sup>
CABLE MATERIAL	PVC H03VVF	CABLE MATERIAL	PVC H03VVF
CABLE COLOUR	BLACK	CABLE COLOUR	BLACK
CONDUCTOR INSULATION MATERIAL	PVC	CONDUCTOR INSULATION MATERIAL	PVC

TOLLERANZE	DISEGNATORE	DATA	SCALE	DISEGNO N.
UDA1	LIBERAZIO CONTROLLO	13-10-10	1 : 1	
DESCRIZIONE		TR0	CP1	MATERIALE
DIN43650/C,2POLES+EARTH(6/12), WITH RED LED+DIODE, 24V, WITH CABLE PVC/PVC,H03VVF,3X0.5mm <sup>2</sup> ,BLACK,L=2m				
HIGH TECH PRODUCTS		HIGH TECH PRODUCTS		
CP1N02DL1C012		CP1N02DL1C012		