


CONTACTS WITH SOLDERING
PROTUBERANCE

CONNECTOR FEATURES	
PRODUCT TYPE	ENT75301-803 FORM A FIELD ATTACHABLE.
HOUSING MATERIAL/COLOUR	PA66 /TRASPARENT
PRESS -CABLE MATERIAL/COLOUR	PA66 /BLACK
INTERNAL CORE MATERIAL/COLOUR	PA66 /BLACK
HEIGHT HOUSING	30mm
CONTACTS SPACING	18mm
CONTACTS TYPE	SCREW CONTACTS
NUMBER OF POLES	2POLES-EARTH
EARTH POSITIONING	H12 (TURNABLE)
CABLE EXIT	1/2" NPTF
MAX. CONDUCTOR SIZE	1,5mm ²
PROTECTION CLASS	IP67
CIRCUIT TYPE	WITHOUT ELECTRONIC
RATED VOLTAGE	250V AC / 300V DC
CONNECTOR TEMPERATURE RANGE	from -40°C to +90°C
GASKET TYPE	PROFILED NBR
FIXING SCREW	M3X0,5 L=32,5mm
CONNECTOR WITH H.T.P. LOGO	

TOLLERANZE	±0,2	DISIGNAZIONE	ROBERTO SUGLIANI	DATA	24-09-2020	SCALA	1:1	PE80
UDM	ANGOLID	CONTROLATO						
DESCRIZIONE CONNECTOR DIN43650/A.G1 SERIES CONTACT SPACING 18mm, 2P-E, TRASPARENT HOUSING WITHOUT ELECTRONIC, 1/2NPTF CONNECTOR WITH H.T.P. LOGO.								
H.T.P. HIGH TECH PRODUCTS							CODE	G1TF2000



H.T.P.
HIGH TECH PRODUCTS

G1TF2000